

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

Objectives:

The objectives of this investigation are to evaluate and monitor the radiometric integrity of the Landsat-D Thematic Mapper (TM) thermal infrared channel (band 6) data and to develop improved radiometric preprocessing calibration techniques for removal of atmospheric effects.

Problems:

To date no 1600 BPI TEM tapes with band 6 data have been received. Since the dedicated computer primarily available for TEM data processing cannot handle 6400 BPI tapes, preliminary program development has been impeded.

Accomplishments:

Upon receipt of contract NAS5-27323, a purchase order was issued to have a filter fabricated to match the spectral response of the Landsat band 6 sensors. This filter has been received and the combined system response function computed. The half power points for the aircraft system are 10.5 and 11.55 μm compared to the 10.4 and 11.5 μm values for the satellite. These discrepancies are considered acceptable, their effect on the apparent temperature observed at the satellite is being evaluated, and the filter has been installed in the infrared line scanner. The line scanner has been installed in the aircraft and field checked. A daytime underflight of the satellite is scheduled for the next clear overpass and the feasibility of a nighttime overpass is being discussed with NASA.

The LOWTRAN 5 computer code has been obtained from the Air Force Geophysical Laboratory and is being implemented for use on this effort.

Significant Results:

None this reporting period.

Publications:

None this reporting period.

Recommendations:

With reference to "Problems" above, we would recommend that 1600 BPI tapes be made available to investigators as soon as possible.